

APPLICATIONS

Industrial (outdoor) –
Open storage, Ports, Quarries,
Production platforms
Urban – Rail depots, Junctions



Product Name	Power Consumption	Lumen Output*	Product Size LxBxH	Weight	Order Reference
ZETA M 12	90W	8630 Lm	360 x 350 x 115 mm	11610 g	ZTM12
ZETA M 16	129W	12274 Lm	360 x 350 x 115 mm	11600 g	ZTM16
ZETA M 20	203W	19465 Lm	360 x 350 x 115 mm	11900 g	ZTM20
ZETA M 40	408 W	38930 Lm	720 x 350 x 115 mm	24000 g	ZTM40

* Values are given for OB2 and may vary for other optic types.

PRODUCT FEATURES

- Ideal replacement for metal halide floodlights.
- Suitable for lighting large areas
- Energy efficient – savings of 70% and more compared to conventional systems
- Controllable – 1-10V, DALI, Standalone control

PRODUCT INFORMATION

Light Colour	3000 – 5000 K
Light Source	Lumileds LUXEON®
CRI	70 – 90
Lifetime	L70: > 60,000 hours (@Ts = 85°C)
Ambient temp	-25°C + 55°C
Mains voltage	90 – 305 VAC
IP protection class	IP66
Made in	EU

DRIVER SPECS

- Dimming – 1-10V, DALI, Standalone control

MATERIALS

Casing – aluminium alloy
Heat sink – aluminium extrusion, anodized
Diffuser – tempered glass (PMMA upon request)
Bracket – steel (316L stainless steel upon request)

ORDER CODE

Colour temperature	3000K	3K
	4000K	4K
	5000K	5K
Optic	Broad	OB2
	Custom	OC

Order code example: **ZTM20-4K-OB2**