

## δ MP

### APPLICATIONS

**Industrial** – Manufacturing, Warehouses, Workshops, Print Works, Cold Stores

**Commercial** – Multistorey car parks, Garages, Retail



Product Name	Power Consumption	Lumen Output*	Product Size LxBxH	Weight	Order Reference
<b>DELTA MP 16</b>	36W	4250 Lm	615 x 100 x 78 mm	2050 g	DLMP16
<b>DELTA MP 24</b>	54W	6370 Lm	915 x 100 x 78 mm	2950 g	DLMP24
<b>DELTA MP 32</b>	72W	8352 Lm	615 x 100 x 78 mm	2100 g	DLMP32
<b>DELTA MP 48</b>	102W	11530 Lm	915 x 100 x 78 mm	3100 g	DLMP48
<b>DELTA MP 64</b>	144W	15840 Lm	1415 x 100 x 78 mm	5920 g	DLMP64

\* Values are given for HEX and may vary for other diffuser types.

### PRODUCT FEATURES

- Ideal replacement for standard low bay lighting systems
- Energy efficient – savings of 70% and more compared to conventional systems
- Easy mount clip-on brackets
- Variety of control options – DSI, DALI, switchDIM, corridorFUNCTION
- High Bay Kit is available for models DELTA MP 24 and DELTA MP 48

### PRODUCT INFORMATION

Light Colour	3000 – 5000 K
Light Source	LG Innotek
CRI	80 – 90
Lifetime	L70: > 60,000 hours (@Ts = 85°C)
Ambient temp	-25°C + 55°C
Mains voltage	220 – 240 V
IP protection class	IP66
Made in	EU

#### HIGH BAY KIT

Allows the product to be used as High Bay fitting\*

40° - 894 x 0.4 mm - DLRf-900-40

60° - 894 x 0.4 mm - DLRf-900-60

\* only available for models DELTA MP 24 and DELTA MP 48

### DRIVER SPECS

- Standard – Non dimming
- Dimming – DSI, DALI, switchDIM, corridorFUNCTION

### MATERIALS

Casing – aluminium extrusion

Diffuser – PMMA

Bracket – steel

### ORDER CODE

Colour temperature	3000K	3K
	4000K	4K
	5000K	5K
Driver type	Standard	ST
	Dimming	D
Diffuser type	Prismatic	HEX
	Frosted	OPQ

Order code example: DLMP24-4K-ST-HEX