

δ ES

APPLICATIONS

Industrial (High Bay) –
Warehouses, Cold stores,
Hangars, Manufacturing
Urban – Tunnels,
Passages



Product Name	Power Consumption	Lumen Output*	Product Size LxBxH	Weight	Order Reference
DELTA ES 16	36W	3640 Lm	615 x 100 x 78 mm	2100 g	DLES16
DELTA ES 24	54W	5450 Lm	915 x 100 x 78 mm	3650 g	DLES24
DELTA ES 32	72W	7270 Lm	915 x 100 x 78 mm	3750 g	DLES32
DELTA ES 48	102W	10710 Lm	1415 x 100 x 78 mm	5490 g	DLES48
DELTA ES 64	144W	13370 Lm	1415 x 100 x 78 mm	5920 g	DLES64

* Values are given for OB and may vary for other optic types.

PRODUCT FEATURES

- Ideal replacement for standard high bay lighting systems
- Variety of lenses available to ensure tailored optimal performance
- Energy efficient – savings of 70% and more compared to conventional systems
- Easy mount clip-on brackets
- Variety of control options – DSI, DALI, switchDIM, corridorFUNCTION

PRODUCT INFORMATION

Light Colour	3000 – 5000 K
Light Source	Lumileds LUXEON®
CRI	60 – 90
Lifetime	L70: > 60,000 hours (@Ts = 85°C)
Ambient temp	-25°C + 55°C
Mains voltage	198 – 264 VAC
IP protection class	IP66
Made in	EU

DRIVER SPECS

- Standard – Non dimming
- Dimming – DSI, DALI, switchDIM, corridorFUNCTION

MATERIALS

Casing – aluminium extrusion
Diffuser – tempered glass (PMMA upon request)
Bracket – steel

ORDER CODE

Colour temperature	3000K	3K
	4000K	4K
	5000K	5K
Driver type	Standard	ST
	Dimming	D
Optic	Broad	OB
	Asymmetrical	OLN1
	Oblate	OLN2
	Wide	OW
	Custom	OC

Order code example: **DLES24-4K-ST-OB**