

## K M

### APPLICATIONS

Industrial (Canopy) –  
Service stations,  
Loading platforms



Product Name	Power Consumption	Lumen Output*	Product Size LxBxH	Weight	Order Reference
<b>KAPPA M 12</b>	90W	8630 Lm	425 x 425 x 175 mm	10050 g	KPM12
<b>KAPPA M 16</b>	129W	12274 Lm	425 x 425 x 175 mm	10100 g	KPM16

\* Values are given for OB2 and may vary for other optic types.

### PRODUCT FEATURES

- Ideal replacement for standard under canopy lighting systems
- Suited for outdoor and indoor applications
- Comes with a package of individually selected precision optics as standard
- Energy efficient – savings of 70% and more compared to conventional systems
- Controllable – 1-10V, DALI, Standalone control

### PRODUCT INFORMATION

Light Colour	3000 – 5000 K
Light Source	Lumileds LUXEON®
CRI	70 – 90
Lifetime	L70: > 60,000 hours (@Ts = 85°C)
Ambient temp	-25°C + 55°C
Mains voltage	90 – 305 VAC
IP protection class	IP66
Made in	EU

### DRIVER SPECS

- Dimming – 1-10V, DALI, Standalone control

### MATERIALS

Casing – aluminium alloy  
Heat sink – aluminium extrusion, anodized  
Diffuser – tempered glass (PMMA upon request)  
Bracket – steel, painted

### ORDER CODE

Colour temperature	3000K	3K
	4000K	4K
	5000K	5K
Optic	Broad	OB2
	Custom	OC

Order code example: **KPM16-4K-OB2**